

Technical Data Pipes Conforming to ASTM A-53* Gr. A & B Sch. 20/40/80

Nominal Bore		Outside Diameter		SCH 10				No. of Pices per Bundle	SCH 40/30*				No. of Pices per Bundle
mm	inch	mm	inch	Wall Thickness		Weight Plain End			Wall Thickness		Weight Plain End		
mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
20	4-Mar	26.7	1.05	2.11	0.083	1.28	0.96	90	2.87	0.113	1.69	1.13	90
25	1	33.4	1.315	2.77	0.109	2.09	1.41	90	3.38	0.133	2.5	1.68	60
32	1 1/4	42.2	1.66	2.77	0.109	2.69	1.81	61	3.56	0.14	3.39	2.27	42
40	1 1/2	48.3	1.9	2.77	0.109	3.11	2.09	61	3.68	0.145	4.05	2.72	36
50	2	60.3	2.375	2.77	0.109	3.93	2.64	37	3.91	0.154	5.45	3.66	26
65	2 1/2	73	2.875	3.05	0.12	5.26	3.53	29	5.16	0.205	8.68	5.8	18
80	3	88.9	3.5	3.05	0.12	6.46	4.34	24	5.49	0.216	11.29	7.58	14
90	3 1/2	101.6	4	3.05	0.12	7.41	4.98	21	5.74	0.226	13.58	9.12	12
100	4	114.3	4.5	3.05	0.12	8.37	5.62	19	6.02	0.237	16.09	10.8	10
125	5	141.3	5.563	3.4	0.134	11.58	7.78	10	6.55	0.258	21.79	14.63	8
150	6	168.3	6.625	3.4	0.134	13.85	9.3	10	7.11	0.28	28.29	18.99	7
200	8	219.1	8.625	4.78	0.188	25.26	16.96	5	7.04*	0.277	36.82	24.72	5